

COTTON BIODEGRADABLE TACKSTRAP®



INSTALLATION NOTES:

INSTALL USING ONE STRAP PER STAKE. OVERLAP STRAP-ENDS TO DESIRED ADJUSTMENT AND STRIKE NAIL INTO STAKE. TRIM OFF EXCESS. ALWAYS HAMMER AWAY FROM THE BODY AND STRIKE THE NAIL SQUARELY ON THE HEAD. SAFETY GOGGLES SHOULD ALWAYS BE WORN WHEN INSTALLING THE TACKSTRAP.

SPECIFICATIONS FOR 3500 SERIES BIODEGRADABLE TACKSTRAP®

Recommended for 2.5 - 5cm, 1- 2in caliper tree
Break Strength: 130kg, 230lbs
Length: 81cm - 132cm, 32in - 52in
Width: 2.54cm, 1in
Weight: .0182kg, .64oz
Color: Natural White
Galvanized nail with green retaining washer: 2.9cm, 1in
Meets US Green Building Council Standard: V4 b,d,c

SPECIFICATIONS FOR 3700 SERIES BIODEGRADABLE TACKSTRAP®

Recommended for 5 -10cm, 2 - 4in caliper tree
Break Strength: 147kg, 325lbs
Length: 81 - 132cm, 32 - 52in
Width: 2.54cm, 1in
Weight: .135kg, 1.22oz
Color: Green (OD) or Natural
Galvanized nail with green retaining washer: 2.9cm, 1in
Meets US Green Building Council Standard: V4 b,d,c